



ATTIC COVERAGE CHART – ALL BORATE STABILIZED CLASS 1 FIRE RATED MATERIAL

Installed Density and Coverage of FRM			FRM100
SF PER BAG			
Target Finished Density (Dry pcf)	8" Cavity	12" Cavity	Minimum Finished Density (Dry pcf)*
4.0	12.0	7.5	3.35

*IF ANY PART OF THE ASSEMBLY HAS A DRY (10% OR LESS MOISTURE BY WEIGHT) DENSITY LESS THAN 3.35 PCF, THE WALL IS NO LONGER AN APPROVED UL TWO HOUR FIRE ASSEMBLY.

Greenfiber® provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, Greenfiber® Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION

This insulation has been installed in conformance with the above recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature

Company Name

Date

Applicator's Signature

Company Name

Date

Manufactured by
US Greenfiber, LLC
Toll-Free 800-228-0024
www.greenfiber.com
Greenfiber is a registered trademark of US Greenfiber, LLC. All rights reserved.
© 2020 US Greenfiber, LLC. All rights reserved.
US Greenfiber, LLC
5500 77 Center Drive, Suite 100
Charlotte, NC 28217

Mesa, AZ 85212
Norfolk, NE 68701
Salt Lake City, UT 84119
Tampa, FL 33605
Waco, TX 76704
Wilkes-Barre, PA 18702
Debert, Nova Scotia

Made in USA

